

**SMALL SIZED INFORMATION DEVICE,
SYSTEM AND METHOD FOR MANAGEMENT OF LENDING OF
SMALL SIZED INFORMATION DEVICES, AND COMPUTER PRODUCT**

5 FIELD OF THE INVENTION

 The present invention relates to a technology of carrying out the operations related to lending of a small sized information device using a terminal connected to a network. The related to lending include reservation of the information device the user wishes to borrow to returning of the borrowed information device. The small sized information device includes a digital still camera, a digital video camera and the like.

15 BACKGROUND OF THE INVENTION

 In recent years, a digital camera has been rapidly promoted as an image inputting device along with the popularization of a personal computer and the Internet and so on. For example, the cases have been increased such that the digital camera is used in a company and an office for taking pictures of progress and results of a business or scenes of an event and a report of a business journey or the like by a digital camera and transmitting these photo data by a mail via a personal computer, an image outputting device or an internet to report them in real time. Thus,

when a company purchases a digital camera and manages lending of the digital camera, a method such that general software is used or a user writes down a lending managing note or the like. Alternatively, most of digital cameras employ
5 a detachable smart medium and a memory card with a limited storage capacity as a recording medium of a pictured image.

Following technical literature disclose related matter. Japanese Patent Application Laid-Open (JP-A) No. 9-319960 discloses a technology to solve a problem in case
10 a user forgets and does not returns a portable information device he/she has borrowed. Japanese Patent Application Laid-Open (JP-A) No. 10-93750 is solves the problem of competitive utilization of a scanner, when a plurality of clients share one scanner, by making a reservation for the
15 scanner. Japanese Patent Application Laid-Open (JP-A) No. 10-164419 relates to a system in which photographing conditions of a camera can be controlled through a network. In JP-A No. 10-164419 when there occurs a double reservation, the fact is informed to the users.

20 However, since a registration operation for lending is complicated on managing lending of a digital camera as described above, there is often the case that the digital camera is lent by a verbal promise. This involves a problem such that it is not possible to know who posses the digital
25 camera now. Alternatively, if the lending management is

carried out severely, this involved a problem such that operation, which is required for lending the digital camera, is increased on each occasion and burden on an administrator is also increased.

5 Alternatively, depending on a standpoint of a user, it is necessary to install driver software or the like in a personal terminal on using a photographed image by a personal computer, so that there is a problem such that the photographed image is not capable of being easily utilized.

10 Additionally, if the images are stored in a detachable medium, burden for managing is further increased. Further, when the stored mediums are distributed individually, the medium is very expensive, so that it involves a problem such that the medium is not economical.

15 According to Japanese Patent Application Laid-Open (JP-A) No. 9-319960, although the lent medium is prevented from being returned, reservation of lending and managing thereof are not carried out. Therefore, competition in reservation of lending occurs. According to Japanese
20 Patent Application Laid-Open (JP-A) No.10-93750 and Japanese Patent Application Laid-Open (JP-A) No. 10-164419, an image inputting device, which is used with being always connected, such as a scanner via a network or a device to be used with being connected are booked, so that they are
25 not used with the connection from the system released.

SUMMARY OF THE INVENTION

It is one object of this invention to share efficiently a small size information device and decrease the operation for managing lending of the small size information device.

5 It is an another object of the present invention to enable distribution of images without installing a dedicated drive software in a terminal and using a conventional medium by taking images from the small size information device from a server and transmitting the images to the terminal in
10 accordance with a transmission method on reservation.

According to one aspect of the present invention, for example, on using the digital camera, a user of the digital camera performs the input operation for reservation from a client terminal, which is connected to a network, to a
15 server terminal and the server terminal registers reservation of the digital camera and lend it depending on reservation input information from the client terminal, so that the reservation, the lending and management thereof are systemized and the lending reservation becomes capable
20 of being inputted on the client terminal.

According to another aspect of the present invention, for example, on using the digital camera, a dedicated client software is not used but a WWW server is installed on the server terminal to build a system on a WWW. Then, the client
25 terminal activates a general WWW browser and the user inputs

a URL of the server terminal, so that a lending reservation page of the small size information device is displayed and the input operation is capable of being performed on this lending reservation page.

5 Other objects and features of this invention will become apparent from the following description with reference to the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

10 Fig. 1 is a block diagram showing a constitution of a digital camera lending management system according to an embodiment of the present invention;

 Fig. 2 is a block diagram showing an internal constitution of the digital camera in Fig. 1;

15 Fig. 3 is a block diagram showing an internal constitution of a digital camera server in Fig. 1;

 Fig. 4 is an explanation drawing of an example of a main panel of a lending reservation client according to the embodiment of the present invention;

20 Fig. 5 is an explanation drawing of a user certification dialogue box of the lending reservation client according to the embodiment of the present invention;

 Fig. 6 is an explanation drawing of a reservation success dialogue box of the lending reservation client
25 according to the embodiment of the present invention;

Fig. 7 is an explanation drawing of a reservation failure dialogue box with respect to a failure of the certification on lending reservation according to the embodiment of the present invention;

5 Fig. 8 is an explanation drawing of a reservation failure dialogue box, in the case that the reservation desired date is already reserved, on lending reservation according to the embodiment of the present invention;

Fig. 9 is an explanation drawing showing a panel example
10 for reservation inspection and reservation cancellation according to the embodiment of the present invention;

Fig. 10 is a flowchart showing a reservation processing example according to the embodiment of the present invention;

Fig. 11 is a flowchart showing a lending processing
15 example according to the embodiment of the present invention;
and

Fig. 12 is a flowchart showing a restoration processing example according to the embodiment of the present invention.

20 DESCRIPTION OF THE PREFERRED EMBODIMENTS

Preferable embodiment of the present invention will be explained with reference to the accompanying drawings below. It is assumed here that the small sized information device is a digital camera. However, the present invention
25 is not limited to this embodiment.

According to the present invention, upon using the digital camera, a user manages the operation from lending reservation to restoration via a terminal, which is connected to the network. The summary of the present invention is as follows. At first, a digital camera server terminal receives lending reservation, which is accessed from the terminal, and manages it. Then, when the user wishes to use the digital camera in actual, the digital camera server terminal checks the user's certification by the IC card and the password or the like and the reservation. If the check is successful, the digital camera server terminal transmits a setting signal, which is capable of being used by the digital camera, to the digital camera. After that, when the user returns the digital camera, the digital camera server terminal reads the image data and transmits the image data by a transmission method, which the user desires, in accordance with reservation. The constitution and the operation of the system will be explained below.

Fig. 1 is a block diagram showing a constitution of a digital camera lending management system according to an embodiment of the present invention. Fig. 2 is a block diagram showing an internal constitution of the digital camera in Fig. 1. Fig. 3 is a block diagram showing an internal constitution of a digital camera server in Fig. 1.

In this system, a digital camera 10 is connected on a LAN 50 by a cable 45 and a digital camera server 20 for managing lending reservation of the digital camera 10 and a client terminals 40a and 40b for reserving (accessing) lending of the digital camera 10 are connected on the LAN 50 in a broad sense. A printer is connected to the LAN 50 (not illustrated). Fig. 1 shows only one digital camera 10, however, a plurality of digital cameras may be provided. When there are many digital cameras, all the cameras may of the same type or each digital camera may be of different type. Further, the digital camera 10 is shown to be connected to the digital camera server terminal 20 through the cable 45, however, the digital camera 10 may be made to communicate with the digital camera server terminal 20 using radio waves such as infrared rays.

The digital camera server terminal 20 comprises a serial port I/F 21, a digital camera driver 22, a display device 23, an IC card reader 24, a reservation checking section 25, a user certification section 26, an image transmission section 27, a reservation managing section 28, a reservation database (DB) 29, a user database (DB) 30 and a network I/F 31.

The serial port I/F 21, for example, uses a serial interface such as an RS-232C or USB (Universal Serial Bus) or the like. When reserving or after returning the digital

camera, the I/F section of the digital camera 10 and the digital camera server terminal 20 are connected by the cable 45 to transmit a predetermined signal to the digital camera 10. The digital camera driver 22 controls a whole of the digital camera server terminal 20 collectively. The display device 23 displays information associated with lending reservation/restoration.

The IC card reader 24 is a device which reads the ID (identification number) of a user when the user inserts his/her IC card in it. The reservation checking section 25 has a function for checking the reservation status and displaying the status on the display device 23. The user certification section 26 authenticates the user ID (and a password and fingerprint or the like), which is inputted by the IC card reader 24, by searching the user information, which is stored in the user database 30.

The image transmission section 27 reads the image data from the digital camera 10 and transmits the images in accordance with setting. The reservation managing section 28 manages lending reservation and restoration and so on in accordance with information, which is transmitted from the client software via the network I/F 31, and information, which is stored in the reservation database (DB) 29.

Alternatively, as shown in Fig. 3, the digital camera server terminal 20 comprises a lock control section 32 for

transmitting a lock/release signal of the digital camera
10 in accordance with success/failure of reservation
checking, an image inputting section 33 for inputting the
images from the digital camera 10 via the serial port I/F
5 21, a WWW (World Wide Web) server 34 for searching a Web
page by a HTTP (Hyper Text Transfer Protocol) and a
reservation status transmission section 35 for transmitting
the reservation status. Alternatively, the WWW server 34
may be installed according to need.

10 The present embodiment will be explained taking a
system in accordance with the IC card using the IC card reader
24 and its password as an example. However, in addition
to the above system, a system in accordance with a well known
magnetic card and a system in accordance with fingerprint
15 checking may be used. In other words, in the case of the
magnetic card, a magnetic card reader may be provided in
place of the IC card reader 24 and in the case of the
fingerprint, a fingerprint image inputting device may be
provided in place of the IC card reader 24.

20 AGUI (graphical user interface) of the client software,
which is described later in Fig. 4 to Fig. 9, is installed
in the client terminals 40a and 40b.

As shown in Fig. 2, in the digital camera 10, an image
inputting (photography or shooting) section 12 for inputting
25 images by a lens and CCD or the like, an image storing section

13 for storing photographed images, an image displaying
section 14 for displaying the case of monitoring the images,
a lock section 15 for realizing the lock function such as
photography possible/photography impossible by a signal
5 from the outside, an available time management section 16
for managing the time, which is available by reservation
lending and an available time displaying section 17 for
displaying the time, which is available by reservation
lending and an image transmission section 18 for transmitting
10 the images to the digital camera server terminal 20 are
connected to a camera control section 11 for controlling
a full body of the camera.

Operation of the digital camera lending management
system and the digital camera will be explained with
15 reference to explanation diagrams shown in Fig. 4 to Fig.
9 and flowcharts shown in Fig. 10 to Fig. 12 in the order
of reservation, lending, restoration, confirmation of
reservation status and cancellation of reservation. Fig.
4 illustrates a main dialogue box, Fig. 5, a user
20 certification dialogue box, Fig. 6, a reservation success
dialogue box, Fig. 7, a reservation failure dialogue box
with respect to failure of certification, Fig. 8, a
reservation failure dialogue box in the case that the
reservation desired date is already reserved, and Fig. 9,
25 a reservation inspection and cancellation panel,

respectively. Additionally, a whole window is referred to as a dialogue box and an enflamed section is referred to a button. This button is clicked to be selected (inputted).

The reservation processing will be explained below.

5 At first, operating any one of the client terminals 40a and 40b, a main dialogue box 50 is displayed. A digital camera selection 51 for selecting a digital camera name, a reservation desired date 52, a transmission method 53, an address 54 and a reservation button 55 are displayed on the
10 main dialogue box 50. They are capable of being inputted.

In the main dialogue box 50 in Fig. 4, selecting the name of the digital camera, inputting the reservation desired date (lending date, restoration date), the transmission method and the address, the reservation button 55 is clicked.

15 Then, a dialogue box 56 for the user certification is displayed (Fig. 5). Here, a user ID 57 and a password 58 are inputted. If the input is correct, an OK button 59 is clicked and if it is incorrect or it should be cancelled, a cancel button 60 is clicked. Alternatively, after
20 inputting the user ID and the password, if the user wishes to continue the reservation, the OK button 59 is clicked and if the user does not wish to continue the reservation, the cancel button 60 is clicked.

Inputting the user ID and the password, the reservation
25 desired date, the transmission method, the user ID and the

password are transmitted from the client terminals 40a and 40b to the digital camera server 20 via the LAN 50. The digital camera server 20 receives the above described input information, respectively to display in accordance with reservation success/reservation failure. In other words, when the input information is correct and the reservation is not overlapped (competed), a reservation success dialogue box 61 indicating "reservation is accepted" is displayed as shown in Fig. 6.

On the other hand, when the inputted user ID and the password are found to be incorrect as a result of the certification, a reservation failure dialogue box 62 indicating "the user certification is failed" is displayed as shown in Fig. 7. Alternatively, when another reservation is already registered in the inputted reservation desired date, a reservation failure dialogue box 63 showing "another reservation is already registered in the inputted reservation desired date" is displayed as shown in Fig. 8.

Fig. 10 is a flowchart showing the operation of reservation processing. At first, in the digital camera server 20, the reservation managing section 28 receives the reservation information, which is transmitted from the client software via the network I/F 31 (step S11). In this case, if the reservation information is encrypted, it will be decrypted. Then, transmitting the user ID and the

password to the user certification section 26, the user certification section 26 checks them with the user database 30 to authenticate them (step S12), so that it is judged whether the user is found or not (step S13), in other words,
5 the user certification is carried out.

In the case that it is confirmed that the user ID exists in the user database 30 and it is judged that the user is found, the password is checked (step S14). After that, it is judged whether the inputted password is correct or not
10 (step S15). In this case, if the password is judged to be correct, the reservation database 29 is searched with respect to a reservation desired date (step S16).

As a result of the above search, it is judged whether the reservation of the reservation desired date exists or
15 not (step S17). In this case, if it is judged that the reservation desired date is not reserved in the reservation database 29, the reservation information is stored in the reservation database 29 (step S18) and reservation completion information is transmitted to the client terminal
20 (step S19). Alternatively, in the case that the reservation is successful, the reservation success dialogue box shown in Fig. 6 is displayed.

On the other hand, in the case that it is judged that the user is not found in the above step S13, or the password
25 is incorrect in the above step S15, or the reservation is

overlapped in the above step S17, error information is transmitted to the client software (step S20). The client software displays the reservation failure dialogue box shown in Fig. 7. Alternatively, in the case that the reservation date is overlapped, the client software displays the reservation failure dialogue box shown in Fig. 8.

In the mean time, checking with a directory server, which is connected to the network when the user database 30 is not provided in the digital camera server 20, the user certification as same as the above may be carried out. Alternatively, if the client software has a function to store setting such as a transmission method or the like in a file or the like, a desired setting will be easily performed by reading the stored file.

15 Additionally, when the client software has a function to search the available digital camera server terminal 20 automatically, even in the case that the user of a mobile terminal such as a note PC or the like connects one's PC to the network away from home, searching the near digital camera server terminal 20 and setting the transmission method usually enable the digital camera to be reserved. Alternatively, in this case, it is assumed that the same kind of digital camera server 20 is also connected to the network away from home. Further, if the transmission of 25 the reservation information to the digital camera server

20 needs more security, the reservation information may be encrypted.

Other than using the dedicated client software in the above described reservation processing, installing the WWW server 34 (see Fig. 3) in the digital camera server 20, a system may be built on the WWW. In this case, the client terminals 40a and 40b activate the general WWW client software (browser software) and the user inputs a URL (uniform resource locator) of the digital camera server 20 to access the digital camera server 20. As a result, the same page as that in Fig. 4 will be displayed.

The operation performed when lending the digital camera 10 will now be explained. Fig. 11 is a flowchart illustrating the lending processing. At first, the user inserts the IC card, in which one's user ID is stored, into the IC card reader 24, which is housed in the digital camera server 20 (step S21). The user certification section 26 reads out the user ID through the IC card reader 24 (step S22) and the user certification section 26 checks (searches) the user database 30 with respect to the corresponding user ID (step S23).

As a result of searching in the above step S23, it is authenticated whether the user ID read in the user database 30 exists or not, in other words, it is judged whether the user is found or not (step S24). If the certification is

failed, a message indicating the digital camera is not available is displayed on the display device 23 (step S30). On the other hand, in the case that it is judged that the user is found, the reservation managing section 28 searches
5 the reservation database 29 with respect to the user ID (step S25) to return the result to the reservation checking section 25.

Consequently, the reservation checking section 25 judges whether the reservation is found or not from the result
10 of the above step S25 (step S26). In this case, if it is judged that the reservation is not found, in other words, it is judged that the reservation is not registered, this is displayed on the display device 23 (step S30). On the other hand, if the reservation is registered, the reservation
15 checking section 25 compares the current time with a reserved time to judge whether the current time corresponds to the reserved time or not (step S27). In this case, if the both of times do not correspond to each other, a message that the both of times do not correspond is displayed on the display
20 device 23 (step S30).

When the two time parameters correspond to each other in the above step S27, the lock of the digital camera 10 is released (step S28). In other words, if the reservation checking is successful, the lock/release signal is
25 transmitted to the digital camera 10. Alternatively, the

lock/release signal includes the information of the reservation date. After that, the digital camera 10 is detached from the cable 45 (step S29).

Thus, lending of the digital camera 10 is successful
5 and the user is capable of detaching the digital camera 10 from the cable 45 and using it. If the used time is over the reserved time, the user is not capable of using the digital camera 10 again. A display panel of the digital camera 10 is capable of displaying rest of the used time. If the used
10 time is over, the display panel of the digital camera 10 displays a message for encouraging returning the digital camera 10. Hereinafter, it becomes impossible to take a picture and store the photograph even pushing a release button.

15 The operation performed when returning the borrowed digital camera 10 will now be explained below. At first, the user concludes using the digital camera 10 and connects the digital camera 10 to the cable 45 of the digital camera server 20 again (step S31) to return the digital camera 10.
20 When the digital camera 10 is returned, the reservation managing section 28 takes in the image transmission method from the reservation in execution to set the image transmission method by the image transmission section 27 (step S32).

25 In accordance with the image transmission method,

which is set, at first, the digital camera 10 takes in the image (step S33) to transmit the image, which is taken in (step S34). After that, locking the digital camera 10 (step S35), the reservation which has been executed is deleted
5 from the reservation database 29 (step S36).

Alternatively, the followings may be used as the image transmission method. For example, the image may be transmitted by attaching it to an email. In this case, encoding the image and attaching it to the email, the encoded
10 images are transmitted to the designated mail address. As a second method, the image may be transmitted through FTP (File Transfer Protocol) server, which enables the transference of files between different systems and the transference of different structural files, is used.

15 According to the method by the FTP server, the FTP connection is established with respect to the designated FTP server and the data is transmitted to the designated directory in accordance with the FTP. Alternatively, the FTP comprises a file transfer protocol, which is provided
20 by a TCP/IP (Transmission Control Protocol/Internet Protocol). Making good use of the FTP, it is possible to store the image data in the FTP server without passing through a medium such as a floppy disk and with omitting the labor of the receiver.

25 As another method, a file is uploaded to the designated

directory by using a PUT method (file transfer by a PUT command) of an HTTP (Hyper Text Transfer Protocol) with respect to the HTTP server. As a fourth method, the data may be transmitted to a printer. In this case, the data
5 is transmitted to the designated printer in accordance with the protocol, which is supported by the printer and the data is printed out.

Alternatively, in place of installing the WWW server's function (WWW server 34) in the digital camera server 20
10 and transmitting the image data, a method for storing the data in the digital camera server terminal 20 may be used. In this case, using the WWW browser from the client terminals 40a and 40b and accessing the digital camera server terminal 20, the image data is capable of being inspected.

15 The operation performed when checking the reservation status and cancellation of the reservation will be explained below. Setting a function for confirming the reservation status and canceling the reservation, a more usable system is realized. Fig. 9 shows a panel example for reservation
20 inspection and reservation cancellation. The client software displays a panel as shown in Fig. 9. If the user selects the data, the reservation status of the designated date is displayed by a graph and a list, which are indicated graphically along a time axis. Clicking (highlighting) the
25 reservation, which is registered by the user oneself in the

list and clicking the reservation cancellation button, the client software requires the reservation cancellation with respect to the digital camera server terminal.

Thus, according to the above described embodiment,
5 on using the digital camera 10, it is not possible to take a picture by the digital camera 10 unless the digital camera 10 is reserved to release the lock function thereof. Alternatively, when the reserved time is over, the function of the digital camera 10 is not capable of being used again,
10 so that it is possible to prevent the digital camera 10 from being missing as it is not returned. Since the all reservation/lending operation is computerized, it is possible to decrease extremely the management operation of lending.

15 Although the user is required to perform the accessing operation for reservation, the labor for moving the photographed images to the user's PC and installing the device driver is decreased, so that the user is capable of using casually the digital camera. Therefore, according
20 to this embodiment, it is possible to share the digital camera efficiently.

Additionally, a combination of the digital camera server terminal 20 (the lending reservation management server) and the digital camera 10 (a device provided with
25 a lock function) according to the present embodiment is

capable of being used efficiently in the lending management
of devices other than the digital camera 10, for example,
a portable terminal, a portable telephone, a game machine
or a PC provided with a camera function and a mobile device
5 or the like.

As explained above, with respect to a small sized
information device lending management system according to
one aspect of the present invention, for example, on using
the digital camera, the user of the digital camera performs
10 the reservation input operation with respect to the server
terminal from the client terminal, which is connected on
the network and the server terminal registers the reservation
of the digital camera and lends it in accordance with the
registration input information from the client terminal,
15 so that the operation from reservation to lending and
management thereof is systemized and it becomes possible
to input for reservation of lending on the client terminal.
Therefore, the digital camera is capable of being shared
efficiently via the network and the managing operation (work)
20 from lending to restoration thereof is capable of being
decreased.

According to the small sized information device
lending management system according to another aspect of
the present invention, for example, on using the digital
25 camera, the dedicated client software is not used, the WWW

server is installed on the server terminal to build a system
on the WWW, the client terminal activates a general WWW
browser and the user inputs the URL of the server terminal,
so that a lending reservation page of the small sized
5 information device is displayed and the input operation is
capable of being performed in the lending reservation page.
Therefore, the digital camera is capable of being lent,
managed and shared efficiently by the terminal on the network
and the managing operation (work) from lending to restoration
10 is capable of being decreased.

Furthermore, in the case that the server terminal
authenticates the user and the user certification is
successful, checking the user with the reservation status
to confirm the reservation registration, the digital camera
15 is lent. Therefore, if the user who does not register the
reservation yet tries to use the digital camera, it is not
possible to borrow the digital camera by means of the user
certification. As a result, accurate lending and managing
thereof are realized.

20 Furthermore, in the case of authenticating the user,
checking the inputted user ID and the password with the user
information, which is already registered in the user base
in advance, the user certification is capable of being
performed reliably. Therefore, the case that the digital
25 camera is lent to the user who does not register the

reservation by mistake is avoided.

Furthermore, as the user certification, the magnetic card is used to check the user ID and the password, which are registered in the magnetic card with the user information, which is registered in the user base in advance, so that the user certification and lending are realized by the rather low-cost magnetic card.

Furthermore, as the user certification, the IC card is used to check the user ID and the password, which are registered in the IC card with the user information, which is registered in the user base in advance, so that the certification data becomes more reliable than the data in the magnetic card. Therefore, more reliable user certification and lending management are realized.

Furthermore, as the user certification, the fingerprint certification is used to check the user ID and the password, which are registered in the IC card with the user fingerprint, which is registered in the user base in advance, so that the IC card or the like is not needed and the user simply puts one's finger on the fingerprint image inputting section. Therefore, a simple and reliable lending management is realized.

Furthermore, for example, on lending the digital camera after registration of lending reservation thereof, the lock of the digital camera is released after the user

certification is successful, so that when the user who does not registers the reservation tries to use the digital camera, the digital camera is locked and it becomes possible that the case the digital camera is used without permission is prevented.

Furthermore, for example, on reserving the digital camera, a method for transmitting the images are designated and the server terminal transmits the images via the network in accordance with the transmission method, which is designated at reservation on returning the digital camera, so that the images are transmitted not via a medium but via the network when the images are distributed to individuals by using a storage medium such as a conventional smart medium or the like. Therefore, the digital camera is capable of being managed rather simply and the cost of the medium is not needed, so that such a small sized information device lending management system is economical.

Furthermore, for example, in the case of transmitting the images, which is taken into the server terminal from the digital camera, to the client terminal, the electronic computer originated mail is used, so that it is possible to receive the images with a simple operation such as a normal mail reception without using the storage medium such as a smart medium or the like in order to distribute the images to the designated address.

Furthermore, for example, in the case of transmitting the images, which is taken into the server terminal from the digital camera, to the client terminal, a FTP (file transfer protocol) to be provided by the TCP/IP is used, 5 so that the image transfer is reliably performed not through a medium such as a floppy disk or the like and even when the receiver does not always attends there.

Furthermore, for example, in the case of transmitting the images, which is taken into the server terminal from 10 the digital camera, to the client terminal, a PUT command (file transfer) of the HTTP is used to transfer the images to the receiver, so that the image transfer is reliably performed not through a medium such as a floppy disk or the like and even when the receiver does not always attends there.

15 Furthermore, for example, the images, which are taken into the server terminal from the digital camera, is outputted to a printing device such as a printer, so that forming the images on a recording paper, which is outputted by the printing device, realizes the image distribution not 20 through a medium such as a floppy disk or the like.

Furthermore, for example, the images, which are taken into the server terminal from the digital camera, is not transmitted to the client terminal but is stored in the WWW server. Then, it is possible that the client terminal 25 accesses the server terminal using the WWW browser and the

images are taken out. Therefore, the user is capable of inspecting the images according to need.

According to the small sized information device of still another aspect of the present invention, for example, since the digital camera is provided with a lock mechanism, by which the digital camera is locked ON/OFF with an external signal, even when the user who does not register the reservation tries to use the digital camera without permission, it is possible to prevent the digital camera from being missing.

Furthermore, the system displays the rest of the reserved time on the displaying device and the camera (device) is locked when the reserved time is over. As a result, priority is given to the use in accordance with the reservation registration and chances such that the reservation use is completed become high.

According to the lending reservation method of still another aspect of the present invention, for example, using a series of operation (work) such as the reservation registration for lending the digital camera, the reservation confirmation on lending of the digital camera and locking on/off of the digital camera as a software, it is possible that the digital camera is shared efficiently via the network and the management operation (work) from lending to restoration of the digital camera is capable of being

decreased.

Furthermore, the images are transmitted from the digital camera via the network in accordance with the designated image transmission method, so that it becomes possible that the images are transmitted to a predetermined receiver's terminal not via a medium but via the network when the images are distributed to individuals by using a storage medium such as a conventional smart medium or the like. Therefore, the digital camera is capable of being managed rather simply and the cost of the medium is not needed, so that such a small sized information device lending management system is economical.

Furthermore, the user is capable of selecting and designating any one of the electronic computer originated mail, the FTP (file transfer protocol) in the TCP/IP, the PUT command (file transfer) of the HTTP, a printer output and a method for storing in the WWW server in accordance with an appropriate method. Therefore, the image distribution is realized by an appropriate method and without the storage medium.

The present document incorporates by reference the entire contents of Japanese priority document, 2000-001134 filed in Japan on January 6, 2000.

Although the invention has been described with respect to a specific embodiment for a complete and clear disclosure,

the appended claims are not to be thus limited but are to be construed as embodying all modifications and alternative constructions that may occur to one skilled in the art which fairly fall within the basic teaching herein set forth.